

CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) An apparatus for sensing remote load voltages, comprising:

a power converter; **and**

a plurality of remote loads, each remote load located in a **respective**

feedback loop connected to the power converter; **and**

a **first one of said** ~~feed-back~~ **feedback** loops **being** connected to the

~~power converter, the feed back loop being~~ **and** physically adjacent to

the power converter, **and a second one of said** ~~wherein the feed back~~

feedback loops **being** ~~further comprises a first path and a second path,~~

~~and the first path and the second path are in parallel~~ **with said first loop;**

said **second** ~~first-loop~~ path being connected to one of said remote loads;

and said ~~second~~ **first loop, path** ~~unlike said second loop,~~ not being

directly connected to any of said remote loads, and having a faster

response than said ~~first~~ **second** ~~path~~ **loop.**

2. (original) The apparatus of **[[c]]C** laim 1, wherein the first path further includes a low-pass filter.

3. (original) The apparatus of **[[c]]C** laim 1, wherein the first path further includes a high-pass filter.

4. (original) The apparatus of **[[c]]C** laim 1, wherein the first path further includes a band-pass filter.

5. (Currently Amended) The apparatus of ~~[[c]]~~Claim 1, further comprising an error amplifier connected to both said ~~the feedback~~ feedback loops.

6. (Currently Amended) An apparatus for sensing remote load voltages, comprising:

a power converter;

a plurality of remote loads, each remote load located in a loop connected to the power converter; ~~and~~

a ~~feed-back~~ **feedback** loop connected to the power converter, the ~~feed-back~~

feedback loop being physically adjacent to the power converter,

wherein the ~~feed-back~~ **feedback** loop further comprises a first path and

a second path, and the first path and the second path are in parallel; ~~and~~

~~further comprising~~ an error amplifier connected to the ~~feed-back~~ **feedback** loop;

wherein the error amplifier has a gain defined by

$G_{av} = (N * K_a) * (\text{weighted average individual loop gains}),$

wherein;

G_{av} is the average gain of the error amplifier,

N is the number of loops, and

K_a is a constant gain adjustment factor.

7. (Currently Amended) The apparatus of ~~[[c]]~~ claim 1 ~~6~~, wherein the first path further comprises a capacitor-resistor network.

8. (Currently Amended) A method for sensing remote load voltages comprising the steps of:

connecting a remote load to a loop to a power converter;

devising an impedance for a ~~feed-back~~ **feedback** loop according to a

weighted factor for the ~~feed-back~~ **feedback** loop; and

connecting ~~the~~**an additional** ~~feed-back~~ **feedback** loop to the power converter,

wherein the **additional** ~~feed-back~~ **feedback** loop is physically closer to the power converter than the remote load; and

wherein the weighted factor is a desired relative feedback loop

gain ~~wherein an additional feedback loop is also connected to the power converter and to the remote load.~~

9. (Cancelled).
10. (New) An apparatus for sensing remote load voltages, comprising:
 - a power converter;
 - a plurality of feedback loops, each respective feedback loop having a specified loop impedance relative to a desired loop gain and connected to an output terminal of the power converter at one end;
 - a plurality of loads, each load situated in a respective feedback loop at a specified distance from the power converter; and
 - an error amplifier;
 - a first one of said plurality of feedback loops including a remote load,
 - a second one of said plurality of feedback loops being in parallel with said first loop and being physically adjacent to said controller;
 - said second one of said plurality of feedback loops being directly connected to a summing node input of the error amplifier.
11. (New) The apparatus of Claim 10, wherein the plurality of loads include at least one of a nearby load, a remote load, a converter terminal voltage and an inductor terminal voltage.
12. (New) The apparatus of Claim 10, wherein the error amplifier includes a gain compensation network having an impedance, Z_f .

13. (New) The apparatus of Claim 10, wherein each load has a critical voltage point and the error amplifier has an output equal to a sum of a plurality of critical voltage points times the gain of each feedback loop to and including the error amplifier, the error amplifier output being defined by

$$E0 = Zf (i1 + i2 + i3 + \dots + iN),$$

wherein Zf is the impedance of a gain compensation network of the error amplifier,

i is the current flowing through a feedback loop, and

N represents the number feedback loops.

14. (New) The apparatus of Claim 10, wherein the error amplifier has a gain defined by

$$Gav = (N * Ka) * (\text{weighted average individual loop gains}),$$

wherein

Gav is the average gain of the error amplifier,

N is the number of loops, and

Ka is a constant gain adjustment factor.

15. (New) A method of sensing a remote voltage in a power converter system, comprising:

determining the importance of a plurality of critical points in the system;
determining an impedance for each of a plurality of feedback loops in the system based on the determined importance of each of the plurality of critical points;
setting the impedance for each feedback loop; and
monitoring a voltage at each critical point from a summing node of an error amplifier.

16. (New) The method of Claim 12, wherein each feedback loop has at least one critical point.

17. (New) The method of Claim 12, wherein the critical point comprises one or more of a remote load, a nearby load, a converter terminal voltage, and an inductor terminal voltage.

18. (New) The method of Claim 12, wherein the impedance is set using a resistor-capacitor network.

19. (New) The method of Claim 12, wherein the determining an impedance comprises first determining a desired relative gain of each feedback loop.

20. (New) The method of Claim 12, wherein setting the impedance for each feedback loop comprising configuring a specific feedback loop response.